



ERSKINETM
ATTACHMENTS, INC.



Tiller/Leveler/Soil Conditioner

FEATURES

- Direct drive design
- Float mount design for a more efficient operation
- Depth changes on-the-go
- Tungsten - carbide teeth
- Solid rubber wheels; with one pin can be raised out of the way for serious digging
- Side plates are adjustable and removable
- Spiraled teeth for windrowing
- Power angling (optional)



Power Tiller/Leveler/Soil Conditioner...

An attachment that pays for itself in a very short amount of time... replacing your hand labor work crew. This versatile unit rakes stones and debris to either side or straight ahead for easy pickup. The aggressive teeth on the large-diameter rotor pulverize soil like an

ordinary tiller, with the benefit of faster ground speed. The counter-rotating rotor moves soil ahead of it as it tills, filling in low spots and chewing off high spots. It creates perfect seedbeds and windrows. This attachment separates rocks, tears up sod, and pulverizes dirt clods. It rakes and tills as deep as 2".



800-437-6912

www.erskineattachments.com



SKID STEER



MINI SKID STEER



COMPACT TRACTOR

Tiller/Leveler/Soil Conditioner Mini #900529



Floating mounting system follows the contour of the ground

EAT•N | Char-Lynn



Optional:
Toggle Control Harness is required if skid steer is **NOT** equipped with attachment control system. Only need when ordering hydraulic angling model.



Optional:
Universal wire harness for hydraulic models with attachment controls.

Direct drive motor gives higher production with lower maintenance

Large solid urethane rubber tires allow easier maneuverability over rough terrain

AVAILABLE OPTIONS

- Hydraulic Power Angling
- Toggle Control Harness
- Universal Wire Harness - (hydraulic model only)
- Factory Installed Faster Flat-Faced Couplers
- Factory Installed Parker Flat-Faced Couplers
- Available Mounting Kits:
 - ASV/Terex (RC/PT30)
 - Bobcat (MT-52/55, 463/S70)
 - Toro Dingo / Vermeer / Boxer / Ditch Witch / Ramrod / Kanga
 - Universal Mounting Plate for skid steers with up to 1000# R.O.C. (rated operating capacity) and within rated flow

STANDARD SPECIFICATIONS

Angling	Manual
Working Width	48"
Working Depth	0-2.5"
Max. Angle (both ways)	25°
Overall Width	56.75"
Overall Length	55.5"
Rated Flow (GPM)	9-15
Weight	470#



ERSKINETM
ATTACHMENTS, INC.

A Legacy of Excellence Since 1948

"Then you will know the truth, and the truth will set you free." John 8:32

Prices and specifications subject to change without notice • F.O.B. the Factory