



**ERSKINE**<sup>™</sup>  
ATTACHMENTS, INC.



## Tree Shears

### FEATURES

- Cuts up to 12" diameter trees
- Near ground cutting
- Shear blade comprised of AR400 abrasion resistance high tensile steel
- Extremely powerful shear cylinder
- Vertical or horizontal cutting positioning
- Pushbar brush guard keeps tree in front of skid steer



Head rotates 90° to vertical position allowing for the cutting and pruning of limbs and bows.

### Cuts Trees, Brush, and Limbs...

The limitless application of this tool allows you to virtually clear any wooded lot or selectively harvest unwanted trees or brush such as mesquite, cedars, dogwood, alders, junipers, and osage orange.



Designed to allow near-ground cutting.



Fell trees can be sectioned for easy removal or clipped to length for firewood or compact loading.



Cuts up to 12" diameter trees.

America's Best Quality-Value Attachments  
**62**  
SIXTY-TWO YEARS  
ANNIVERSARY

**800-437-6912**

[www.erskineattachments.com](http://www.erskineattachments.com)



SKID STEER



MINI SKID STEER



COMPACT TRACTOR

Tree Shears  
#900630



Shown here for vertical cutting

Vertical and Horizontal rotation

Pushbar

Brush guard w/safety mesh prevents stump or debris from entering cab



Unique hook prevents unnecessary slippage and provides better holding

12"

Greaseable pivot points

### AVAILABLE OPTIONS

- Factory Installed Faster Flat-Faced Couplers
- Factory Installed Parker Flat-Faced Couplers

### STANDARD SPECIFICATIONS

Operating Weight	760#
Working Width	45.20"
Working Height (vertical position)	49"
Working Height (horizontal position)	43"
Hydraulic Cylinder	5 x 12 - 3,000 PSI
Shear Blade Specs	Heat Treated AR400 High Tensile Steel
Rotating Head (manual)	90°
Maximum Diameter Cut	12" tree



**ERSKINE**<sup>TM</sup>  
ATTACHMENTS, INC.

*A Legacy of Excellence Since 1948*

*"I will guide you along the best pathway for your life. I will advise you and watch over you." Psalm 32:8*

Prices and specifications subject to change without notice • F.O.B. the Factory